

Mixer / Pump

MX-10

Take control of your refractory installations
When you want it ... How you want it!

Can be used for:

Refractory Pumpcast Applications
Refractory Shotcrete Applications
¾" Aggregate Concrete
¾" Aggregate Shotcrete



Blastcrete Refractory Pumps are the
most economical,
versatile, simple, and safe
Refractory pumps ever built!

b *blastcrete*

Anniston, AL
800-235-4867
www.blastcrete.com



Standard swing out receiving hopper



Reliable shotcrete delivery up to 12 tons per hour



The MX-10 has been the industry standard since 1996.

Features

- 2200 PSI Piston Face Pressure
- 2200 lb. Capacity High Torque Pan Mixer
- Simple Swing Out Receiving Hopper for Easy Access to Swing Tube Section for Cleaning and Maintenance
- Fill Rite Water Meter
- Forklift Tubing Mounted to Lower Hopper for Easy Flat Pack Removal
- 20 ga. Dousing Bucket for Fast Water Introduction
- CE Certification

Options

- 2,000 PSI Hydraulic Pressure Washer
- Vogel Auto Lubrication System
- Spare Tire Mounted
- Pendant or Wireless Remote
- Skid Mounted with Forklift Tubing

Specifications

Pump	3" x 24" Swing Tube
Pumping Pressure	2200 psi
Mixer	2200 lb. Capacity
Output	12 tons per hour
Discharge	3"
Hopper	2500 lb. Capacity
Operating Platform	22 sq. ft.
Crane Pickup	4 point center pickup
Electrical	Solid State
Trailer	Dual 6,000 lb. Axles
Dimensions	204" x 88" x 117"
Weight	9000 lbs.

Power Options

- John Deere 4045T 99 HP Water Cooled Diesel
- Deutz BF4M 2012 102 HP Water Cooled Diesel
- Dual 40 HP Electric Motors