

Pump

X-10

Engineered for long distance pumping and shotcrete applications
Highest pumping pressure in the industry...When you need it!

Can be used for:

- Refractories
- $\frac{3}{8}$ " (10 mm.) Aggregate Shotcrete
- Precision Pressure Grouting
- Faux Rock Construction
- Slab Jacking
- Block Fill



Blastcrete Pumps are the
most economical,
versatile, simple, and safe
concrete pumps ever built!



Anniston, AL
800-235-4867
www.blastcrete.com

Designed for Demanding Shotcrete Applications



Compact Skid Mount Available



Swing Out Hopper for Easy Access to the Swing Tube



Features

2200 PSI Piston Face Pressure for rugged Refractory Pump Cast and Shotcrete Applications

Simple Swing Out Receiving Hopper for Easy Access to Swing Tube Section for Cleaning and Maintenance

Forklift Tubing Mounted to Lower Hopper for Easy Flat Pack Removal

Reliable Solid State Electronics

CE Certification

Power Options

Kubota V3600 66 HP Kubota Water Cooled Diesel
40 HP Electric Motor

Specifications

Pump	3" x 24" Swing Tube (75mm. x 600 mm.)
Pump Pressure	2200 psi (152 bar)
Output	0-12 yd ³ /hr (9 m ³)
Discharge	3" (75 mm.)
Hopper	2,500 lb. Capacity (1130 kg.)
Trailer	Single 7000 lb. Axle (3175 kg.)
Dimensions	156" X 76" X 80" (396 cm. x 200 cm. x 203 cm.)
Weight	4500 lbs (2041 kg.)

Options

2000 PSI Hydraulic Pressure Washer
Auto Lubrication System
Spare Tire Mounted
Pendant or Wireless Remote
Skid Mounted with Forklift Tubing
Spare Flat Pack
Blastcrete Computerized Water Metering System

Note: Output, conveying distance and height will vary depending on the mix, job conditions, mixing speed, pumping speed and diameter of conveying system.

Blastcrete Equipment Company 2000 Cobb Avenue P.O. Box 1964 Anniston, AL 36202
800-235-4867 (Toll Free) 256-235-2700 256-236-9824 (Fax) www.blastcrete.com